

8. REFERENCES

- [1] R. Baeza-Yates, B. Ribeiro-Neto, et al. *Modern information retrieval*, volume 463. 1999.
- [2] C. Bizer, J. Lehmann, G. Kobilarov, S. Auer, C. Becker, R. Cyganiak, and S. Hellmann. Dbpedia-a crystallization point for the web of data. *Web Semantics: science, services and agents on the world Wide Web*, 7(3):154–165, 2009.
- [3] D. M. Blei, A. Y. Ng, and M. I. Jordan. Latent dirichlet allocation. *Journal of Machine Learning Research*, 3:993–1022, 2003.
- [4] J. Chang, J. Boyd-Graber, C. Wang, S. Gerrish, and D. M. Blei. Reading tea leaves: How humans interpret topic models. In *Advances in Neural Information Processing Systems 22*, 2009.
- [5] G. F. Cooper. The computational complexity of probabilistic inference using bayesian belief networks. *Artificial Intelligence*, 42(2):393–405, 1990.
- [6] M. Y. Dahab, H. A. Hassan, and A. Rafea. Textontoex: Automatic ontology construction from natural english text. *Expert Systems with Applications*, 34(2):1474–1480, 2008.
- [7] S. C. Deerwester, S. T. Dumais, T. K. Landauer, G. W. Furnas, and R. A. Harshman. Indexing by latent semantic analysis. *Journal of the American Society of Information Science*, 41(6):391–407, 1990.
- [8] A. El-Kishky, Y. Song, C. Wang, C. R. Voss, and J. Han. Scalable topical phrase mining from text corpora. *Proceedings of the VLDB Endowment*, 8(3):305–316, 2014.
- [9] K. Frantzi, S. Ananiadou, and H. Mima. Automatic recognition of multi-word terms: the c-value/nc-value method. *International Journal on Digital Libraries*, 3(2):115–130, 2000.
- [10] E. Gabrilovich and S. Markovitch. Computing semantic relatedness using wikipedia-based explicit semantic analysis. In *Proceedings of the 20th International Joint Conference on Artificial Intelligence*, pages 1606–1611, 2007.
- [11] W. A. Gale, K. W. Church, and D. Yarowsky. One sense per discourse. In *Proceedings of the Workshop on Speech and Natural Language*, pages 233–237. Association for Computational Linguistics, 1992.
- [12] T. Gotttron, M. Anderka, and B. Stein. Insights into explicit semantic analysis. In *Proceedings of the 20th ACM International Conference on Information and Knowledge Management*, pages 1961–1964, 2011.
- [13] Y. Halpern and D. Sontag. Unsupervised learning of noisy-or bayesian networks. In *Proceedings of the Twenty-Ninth Conference on Uncertainty in Artificial Intelligence*, pages 272–281, 2013.
- [14] S. Hassan and R. Mihalcea. Semantic relatedness using salient semantic analysis. In *Proceedings of the Twenty-Fifth AAAI Conference on Artificial Intelligence*, 2011.
- [15] A. Hulth. Improved automatic keyword extraction given more linguistic knowledge. In *Proceedings of the 2003 Conference on Empirical Methods in Natural Language Processing*, pages 216–223, 2003.
- [16] Q. Le and T. Mikolov. Distributed representations of sentences and documents. In *Proceedings of the 31th International Conference on Machine Learning*, pages 1188–1196, 2014.
- [17] J. Liu, J. Shang, C. Wang, X. Ren, and J. Han. Mining quality phrases from massive text corpora. In *Proceedings of the 2015 ACM SIGMOD International Conference on Management of Data*, pages 1729–1744, 2015.
- [18] Q. Mei, X. Shen, and C. Zhai. Automatic labeling of multinomial topic models. In *Proceedings of the 13th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, pages 490–499. ACM, 2007.
- [19] T. Mikolov, K. Chen, G. Corrado, and J. Dean. Efficient estimation of word representations in vector space. In *Proceedings of Workshop at ICLR*, 2013.
- [20] M. Sanderson and B. Croft. Deriving concept hierarchies from text. In *Proceedings of the 22nd Annual International ACM SIGIR Conference on Research and Development in Information Retrieval*, pages 206–213, 1999.
- [21] Y. Song, H. Wang, Z. Wang, H. Li, and W. Chen. Short text conceptualization using a probabilistic knowledgebase. In *Proceedings of the Twenty-Second International Joint Conference on Artificial Intelligence*, pages 2330–2336, 2011.
- [22] C. Wang, W. Chen, and Y. Wang. Scalable influence maximization for independent cascade model in large-scale social networks. *Data Mining and Knowledge Discovery*, 25(3):545–576, 2012.
- [23] I. Witten and D. Milne. An effective, low-cost measure of semantic relatedness obtained from wikipedia links. In *Proceedings of AAAI Workshop on Wikipedia and Artificial Intelligence: an Evolving Synergy*, 2008.
- [24] I. H. Witten, G. W. Paynter, E. Frank, C. Gutwin, and C. G. Nevill-Manning. Kea: Practical automatic keyphrase extraction. In *Proceedings of the Fourth ACM Conference on Digital Libraries*, pages 254–255. ACM, 1999.
- [25] W. Wu, H. Li, H. Wang, and K. Q. Zhu. Probase: A probabilistic taxonomy for text understanding. In *Proceedings of the 2012 ACM SIGMOD International Conference on Management of Data*, pages 481–492, 2012.
- [26] X. Yin and S. Shah. Building taxonomy of web search intents for name entity queries. In *Proceedings of the 19th International Conference on World Wide Web*, pages 1001–1010, 2010.
- [27] Z. Zhang, J. Iria, C. A. Brewster, and F. Ciravegna. A comparative evaluation of term recognition algorithms. *Proceedings of the Sixth International Conference on Language Resources and Evaluation*, 2008.