

8. REFERENCES

- [1] T. Akiba, Y. Iwata, and Y. Yoshida. Fast exact shortest-path distance queries on large networks by pruned landmark labeling. In *SIGMOD*, pages 349–360. ACM, 2013.
- [2] B. Aleman-Meza, C. Halaschek-Wiener, S. S. Sahoo, A. Sheth, and I. B. Arpinar. Template based semantic similarity for security applications. In *Intelligence and Security Informatics*, pages 621–622. Springer, 2005.
- [3] N. Alon, R. Yuster, and U. Zwick. Color-coding. *Journal of the ACM (JACM)*, 42(4):844–856, 1995.
- [4] Y. Bai, C. Wang, X. Ying, M. Wang, and Y. Gong. Path pattern query processing on large graphs. In *IEEE BdCloud*. IEEE, 2014.
- [5] G. Bhalotia, A. Hulgeri, C. Nakhe, S. Chakrabarti, and S. Sudarshan. Keyword searching and browsing in databases using banks. In *ICDE*. IEEE, 2002.
- [6] D. M. Blei, A. Y. Ng, and M. I. Jordan. Latent dirichlet allocation. *Journal of Machine Learning Research*, 3:993–1022, 2003.
- [7] T. Coffman, S. Greenblatt, and S. Marcus. Graph-based technologies for intelligence analysis. *Communications of the ACM*, 47(3):45–47, 2004.
- [8] D. J. Cook and L. B. Holder. Substructure discovery using minimum description length and background knowledge. *Journal of Artificial Intelligence Research*, pages 231–255, 1994.
- [9] C. Faloutsos, K. S. McCurley, and A. Tomkins. Fast discovery of connection subgraphs. In *SIGKDD*, pages 118–127. ACM, 2004.
- [10] L. Fang, A. D. Sarma, C. Yu, and P. Bohannon. Rex: explaining relationships between entity pairs. *Proceedings of the VLDB Endowment*, 5(3), 2011.
- [11] B. Gallagher. *The state of the art in graph-based pattern matching*. United States. Department of Energy, 2006.
- [12] M. R. Garey and D. S. Johnson. *Computers and intractability*, volume 29. wh freeman, 2002.
- [13] R. Giugno and D. Shasha. Graphgrep: A fast and universal method for querying graphs. In *Pattern Recognition, 2002. Proceedings. 16th International Conference on*, volume 2, pages 112–115. IEEE, 2002.
- [14] E. Hadjiconstantinou and N. Christofides. An efficient implementation of an algorithm for finding k shortest simple paths. *Networks*, (34.2):88–101, 1999.
- [15] J. Hershberger, M. Maxel, and S. Suri. Finding the k shortest simple paths: A new algorithm and its implementation. *ACM Transactions on Algorithms (TALG)*, 3(4):45, 2007.
- [16] V. Kacholia, S. Pandit, S. Chakrabarti, S. Sudarshan, R. Desai, and H. Karambelkar. Bidirectional expansion for keyword search on graph databases. In *VLDB*, pages 505–516, 2005.
- [17] N. Katoh, I. Toshihide, and M. Hisashi. An efficient algorithm for k shortest simple paths. *Networks*, (12.4):411–427, 1982.
- [18] A. Khan, N. Li, X. Yan, Z. Guan, S. Chakraborty, and S. Tao. Neighborhood based fast graph search in large networks. In *SIGMOD*, pages 901–912. ACM, 2011.
- [19] A. Khan, Y. Wu, C. C. Aggarwal, and X. Yan. Nema: Fast graph search with label similarity. In *VLDB*, volume 6, pages 181–192. VLDB Endowment, 2013.
- [20] N. Lao and W. W. Cohen. Relational retrieval using a combination of path-constrained random walks. *Machine learning*, 81(1):53–67, 2010.
- [21] K. Liu, K. Das, T. Grandison, and H. Kargupta. Privacy-preserving data analysis on graphs and social networks, 2008.
- [22] C. Meng, R. Cheng, S. Maniu, P. Senellart, and W. Zhang. Discovering meta-paths in large heterogeneous information networks. In *WWW*, pages 754–764. International World Wide Web Conferences Steering Committee, 2015.
- [23] J. Pearl. Heuristics: intelligent search strategies for computer problem solving. 1984.
- [24] J. Scott, T. Ideker, R. M. Karp, and R. Sharan. Efficient algorithms for detecting signaling pathways in protein interaction networks. *Journal of Computational Biology*, 13(2):133–144, 2006.
- [25] D. Shasha, J. T. Wang, and R. Giugno. Algorithmics and applications of tree and graph searching. In *ACM SIGMOD symposium on Principles of database systems*, pages 39–52. ACM, 2002.
- [26] C. Shi, X. Kong, Y. Huang, P. S. Yu, and B. Wu. Hetesim: A general framework for relevance measure in heterogeneous networks. *TKDE*, 26(10):2479–2492, 2014.
- [27] Y.-K. Shih and S. Parthasarathy. A single source k -shortest paths algorithm to infer regulatory pathways in a gene network. *Bioinformatics*, 28(12):i49–i58, 2012.
- [28] Y. Sun and J. Han. Mining heterogeneous information networks: a structural analysis approach. *ACM SIGKDD Explorations Newsletter*, 14(2):20–28, 2013.
- [29] Y. Sun, J. Han, C. C. Aggarwal, and N. V. Chawla. When will it happen?: relationship prediction in heterogeneous information networks. In *WSDM*, pages 663–672. ACM, 2012.
- [30] Y. Sun, J. Han, X. Yan, P. S. Yu, and T. Wu. Pathsim: Meta path-based top- k similarity search in heterogeneous information networks. *VLDB*, 2011.
- [31] H. Tong and C. Faloutsos. Center-piece subgraphs: problem definition and fast solutions. In *SIGKDD*. ACM, 2006.
- [32] J. R. Ullmann. An algorithm for subgraph isomorphism. *Journal of the ACM (JACM)*, 23(1):31–42, 1976.
- [33] A. Ullrich and C. V. Forst. k -pathA: k -shortest path algorithm. In *IEEE International workshop on High Performance Computational Systems Biology*, 2009.
- [34] M. Wolverton, P. Berry, I. W. Harrison, J. D. Lowrance, D. N. Morley, A. C. Rodriguez, E. H. Ruspini, and J. Thomere. Law: A workbench for approximate pattern matching in relational data. In *IAAI*, volume 3, pages 143–150, 2003.
- [35] J. Y. Yen. Finding the k shortest loopless paths in a network. *Management Science*, (17.11):712–716, 1971.
- [36] B. Zhou, J. Pei, and W. Luk. A brief survey on anonymization techniques for privacy preserving publishing of social network data. *ACM SIGKDD Explorations Newsletter*, 10(2):12–22, 2008.